

Data Sheet

Ultra-Rugged UHF RFID Tag

Fujitsu WT-A546/A548

Wash, dry, track, repeat

Fujitsu's ultra-rugged standard RFID tag is designed for superior performance and durability for flat linen applications. The industrial-strength WT-A546 and WT-A548 RFID Tags were specifically created to withstand high-pressure extractors without sacrificing quality or performance. At just 52.5 or 59.5mm wide and 6.5mm depth, the ruggedized RFID Tag comes in a compact footprint that is smaller than competitor tags. The small form factor allows for insertion into virtually any type of flat linen, with the tag being virtually unnoticeable when installed. Laundries will greatly improve linen processing with near 100 percent accurate reading by leveraging our RFID Tags' innovative technology. All this comes at a cost-effective price so that linen processing facilities can reduce their cost of entry and enhance their bottom line.



Key Features

- Flexible materials ideal for flat linen applications
- Small form factor for simplified attachment
- Lower cost of entry enhances bottom line
- Exceptional durability for washing, drying, dry cleaning
- Suitable for high-pressure extractors up to 60 bar
- Read hundreds of tagged items in a single pass
- Near 100% accuracy rate improves inventory management

Using Fujitsu's UHF RFID tag solutions, commercial and industrial laundries can greatly enhance asset tracking processes and improve efficiency for sorting and tracking flat linen items such as towels, sheets, and pillow cases. UHF technology increases tag read performance to read hundreds of tags in a single pass, making inventory management faster and more accurate. The WT-A546 and WT-A548 RFID Tags were designed to meet industry demand to withstand high-pressure extractors, industrial washing and drying, and rugged environments without losing performance, all in a cost-effective package.



WT-A546/A548 RFID Tag Specifications

	WT-A546	WT-A548
RFID Standard	ISO/IEC 18000-63 (EPC Gen2)	ISO/IEC 18000-63 (EPC Gen2)
Regulations	RoHS: Conforms to RoHS regulations China RoHS: Conforms to Administrative Measure on the Control of Pollution Caused by Electronic Information Products	RoHS: Conforms to RoHS regulations China RoHS: Conforms to Administrative Measure on the Control of Pollution Caused by Electronic Information Products
MRI Safety Information	MR Conditional (Static magnetic field of 1.5-T and 3-T)	MR Conditional (Static magnetic field of 1.5-T and 3-T)
Size & Weight	52.5 (W) x 6.5 (D) x 2.4 (H) mm, 1.0g	59.5 (W) x 6.5 (D) x 2.4 (H) mm, 1.0g
Tag Type	Passive	Passive
EPC Number Area	96 bit/ unlock (pre-written by Fujitsu)	96 bit/ unlock (pre-written by Fujitsu)
Reading Range (Textile*1)	902-928 MHz: 4W eirp 250 cm (Typical) 2W erp 220 cm (Typical) 865.6-867.7 MHz: 2W erp 250 cm (Typical)	902-928 MHz: 4W eirp 400 cm (Typical) 2W erp 360 cm (Typical) 865.6-867.7 MHz: 2W erp 340 cm (Typical)
Reading Range (Rubber Mat)	902-928 MHz: 4W eirp 230 cm (Typical) 2W erp 200 cm (Typical) 865.6-867.7 MHz: 2W erp: 380 cm (Typical)	902-928 MHz: 4W eirp 310 cm (Typical) 2W erp 280 cm (Typical) 865.6-867.7 MHz: 2W erp: 410 cm (Typical)
Tagging	Directly sewing in hem, seam of linen items; Sewing with patch/pouch	Directly sewing in hem, seam of linen items; Sewing with patch/pouch
Estimated Lifetime	200 washing cycles or 3 years from shipping date, whichever comes first*2	200 washing cycles or 3 years from shipping date, whichever comes first*2
Washing Method	Laundry (PERC and Petroleum based solvents) *3	Laundry (PERC and Petroleum based solvents) *3
Water Extraction Pressure	60 bar	60 bar
Chemical Resistance	Standard Detergent, Softener, Bleach (Oxygen/Chlorine*4), Alkali, Acetic/Peracetic Acid	Standard Detergent, Softener, Bleach (Oxygen/Chlorine*4), Alkali, Acetic/Peracetic Acid
Autoclave Sterilization	121 °C, 15-20 minutes, 80 cycles *5	121 °C, 15-20 minutes, 80 cycles *5
Heat Resistance	Drying: 85 °C (Up to 60 min.) or 120 °C (Up to 10 min.) Ironing: 200 °C (Up to 10 sec. with press cloth)	Drying: 85 °C (Up to 60 min.) or 120 °C (Up to 10 min.) Ironing: 200 °C (Up to 10 sec. with press cloth)
Temperature/Humidity	Operating: -20 to 50 °C, 10 to 95% RH Storage: -40 to 55 °C, 8 to 95% RH	Operating: -20 to 50 °C, 10 to 95% RH Storage: -40 to 55 °C, 8 to 95% RH

All data are results performed in our test condition according to Japan Industrial Standard JIS L 0217 - 102, 301, 401, 402. Your test result may vary.

*1: Reading distance with the condition that textile and attached tag are dry

*2: When used according to the specification, unless otherwise noted

*3: Dry cleaning cycle time is once per day

*4: The tag has been tested 10 times under the conditions in the JIS L 0856 Severe test

*5: This test was conducted under Fujitsu Frontech's laboratory

Contact Positek RFID

Address: 1210 Stanbridge St #710, Norristown, PA 19401

Phone: 610-275-2905

Email: sales@positekrfid.com

Website: www.positekrfid.com/wt-a546-rfid-tag



©2023 Copyright Fujitsu Frontech North America Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks. All other trademarks are the property of their respective owners. Statements herein are based on normal operating conditions and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Frontech North America Inc. reserves the right to modify, at any time without notice, these statements, our services, products, and their warranty and performance specifications.